

# PRODUCTS CATALOGUE

Strapping tool series

Strapping machine series

Case sealer series

Case erector series

Transparent film three-dimensional packing machine series

Stretch wrapper series

Shrink packing machine series

Flap carton sealer series (hot melt glue)




**Strapping tool series**

Product Name	PICTURE	TECHNICAL SPECIFICATIONS	PACKAGING
A6 PP/PET pneumaticl strapping tool		A4 for the bandwidth 9.5-16mm A6 for the bandwidth 13-19mm A8 for the bandwidth 19-25mm Applied with a thickness 0.4-1.5mm Machine Rally 3200N Frictional heat welding connection Air pressure 5.0-7.0kg/cm <sup>3</sup> Machine size 275 × 115 × 113mm Weight 3.9kg	Carton
ZP92 battery powered PET strapping tool		Weight 2.9kgs Max tension 250kgs Applicable Material PET / PP For Bandwidth 9-16mm Applicable generous 0.55-1.35mm Packing efficiency of 300 -500 Charging time 30 minutes Power Source 18V 3000mAh lithium battery	Carton
ZP96 battery powered PET strapping tool		Weight 2.9kgs Max tension 400kgs Applicable Material PET / PP For the bandwidth 16-19mm Applicable generous 0.55-1.35mm Packing efficiency of 300 -500 Charging time 30 minutes Power Source 18V 3000mAh lithium battery	Carton
P322 battery powered PET strapping tool		Applied with a thickness 0.4-1.05mm For the bandwidth 10-16mm Frictional heat welding connection Tightening tension 2400N Weight 4.3kg	Carton




<p>GND16&amp;19 pneumatic steel strapping handle tool</p>		<p>Model GN-16 &amp; GN-19 Brand Origin GUONUO For the bandwidth 16-19mm(choose ) Applied with a thickness 0.38-0.63mm Tightening tension 4500N Connection single bite buckle Weight 4.6kg (including jib) 10</p>	<p>Carton</p>
<p>GN25&amp;32气 pneumatic steel strapping handle tool</p>		<p>Model GN-32 Brand Origin China Apply pressure 0.42 - 0.6Mpa Applied with a thickness 0.8-1.0mm For the bandwidth 25-32mm Maximum tension 7000N Rally jaws 9000N</p>	<p>Carton</p>
<p>MH35 steel strapping handle tool</p>		<p>Model MH-35 Origin Taiwan For the bandwidth 16-19mm Applied with a thickness 0.55- 0.75mm Connection yin and yang buckle (buckle-free) Max tension 8000N Weight 4.2kg</p>	<p>Carton</p>
<p>MH32 steel strapping handle tool</p>		<p>Model MH-32 For the bandwidth 13-19mm Applied with a thickness 0.38-0.63mm Connection yin and yang buckle (buckle-free) Manual operation Weight 3.7kg</p>	<p>Carton</p>





<p>LY-32 pneumatic steel strapping handle tool</p>		<p>Pneumatic strapping locking device Model LY-19 &amp; 25 &amp; 32 Air pressure 0.45-0.6Mpa Steel specification (25-32) ×(0.8-1.2)mm Lock buckle form Lock part of tensile strength ≥16.8KN Weight 3.2kg Strapping Material Steel Pneumatic strapping tensioner Air pressure 0.4-0.6Mpa steel specification (25-32) × (0.8-1.2)mm Strip tension speed 5m/min Tensioning ≥ 9.8KN/0.6Mpa Weight 4.3kg</p>	<p>Carton</p>
<p><b>Strapping machine series</b></p>			
<p>D53 Semi-Automatic Strapping Machine</p>		<p>Power 220V/110V/50HZ/1 phase Power 0.66KW Maximum contraction force 60kg PP width 6-15mm Minimum packing material 60mm Maximum packing material limitation Strapping Speed 1.5 seconds /section PP tape paper core diameter 200mm/230mm/280mm Machine size L895 × W565 × H720-870mm Machine weight 85kg</p>	<p>Wood case</p>
<p>D-301B Full-automatic Low-mesa Strapping Machine</p>		<p>Power 380V/50HZ Machine power 1600W Strapping speed 2.0Sec./Strap Maximum force tied tight 80kg For PP with a wide 9-15mm thick 0.5-1.0mm Bow Frame Size W850 × H600mm Machine Size L1880 * W600* H1200mm Machine weight 280kg</p>	<p>Wood case</p>

<p>D-103C Automatic Strapping Machine</p>		<p>Power 220V/50Hz Power 0.66kw Maximum contraction force 60kgs PP tape paper core 200mm Weight 80kgs</p>	<p>Wood case</p>
<p>D53L semi- automatic PP strapping machine</p>		<p>Model D53L Power supply 380V 50Hz220v/110v/50hz/1 phase Machine power 0.66KW Strapping speed 1.5Sec./Strap Minimum packing material :6-15mm Maximum packing material: Open Applicable PP width 6-15mm PP tape paper core diameter: 200mm/230mm/280mm Machine weight 85kg</p>	<p>Wood case</p>
<p>WK02-30 paper and film tape banding machine</p>		<p>Applicable tape paper &amp; OPP tape Strapping width 30mm Maximum bundle size 410*200mm Minimum size 30*5mm strapping within the core size 40mm Strapping speed 1560/hour Strapping tension 5-40N Machine dimension 560 x 446 x1138mm Net weight 71kg</p>	<p>Wood case</p>

<p>WK01-30 paper and film tape banding machine</p>		<p>Model WK01-30            Machine size 590 × 350 × 510mm(body)            Machine's weight about 35kg            Tied tight packing maximum force 40N            Maximum package size W 380*H200mm            Minimum package size W40 × H 40 mm            Use material OPP and paper tape            Packaging capacity of 400 bags/hour            Thermal fusion bonding mode mode (using a special bonding method, beautiful solid)            Strapping speed 2 seconds /second            Packaged with dimensions 30mm            Power 0.08KW</p>	<p>Wood case</p>
<p>D-301C side automatic strapping machine</p>		<p>Model D-301C            Power supply 220/380V 50/60Hz            Machine power 850W            Strapping speed 2sec/strap            Tied tight power 5-80kg            Applicable PP tape width 9-16mm thick 0.5-1.0mm            Bow Frame Size W600 × H1450mm            Dimension L1610 × W625 × H1840mm            Machine weight 255kg</p>	<p>Wood case</p>
<p>D-310C low-tabletape automatic strapping machine</p>		<p>Model D-310C            Use the power 3PH-220V/380V 50/60Hz            Machine power 850W            Strapping speed 2sec/strap            Tied tight power 5-80kg            Applicable PP tape width 9-16mm thick 0.5-1.0mm            Bow Frame Size W850 × H600mm            Dimension L1880 × W600 × H1200mm            Machine weight 280kg            Table height 450mm</p>	<p>Wood case</p>








<p>D-301B side automation strapping machine</p>		<p>Model D-301B          Use the power 380V/50HZ          Machine power 1600W          Strapping speed 2.0Sec./Strap          Maximum force tied tight 80kg          Applicable PP tape width 9-15mm thick 0.5-1.0mm          Bow Frame Size W850 × H600mm          Dimension L1880 × W600 × H1200          Machine weight 280kg</p>	<p>Wood case</p>
<p>D-102 automation strapping machine</p>		<p>Power: 380V/50Hz 750W/5A (220V to be customized)          Packing speed ≤ 2.5 sec / channel          Table height 750mm          Frame size width 800mm * height customized according to needs          Packing type 1 multi-channel parallel, a little way, manual, and even hit the ball switch, foot switch          Application package with thick (0.55~1.2) mm * Width (9 ~ 15) mm (actual customized by the user)</p>	<p>Wood case</p>
<p><b>Case sealer series</b></p>			
<p>GNA -05 Automatic sealing machine</p>		<p>The machine model GNA-05          Conveyor speed 700-1200pcs/h          Maximum size of package L ∞ x W500 x H500mm          The minimum package size L150 x W100 x H100mm          The power supply for 110V/220V 50/60Hz          machine size L1020* W850*H1350mm          Applicable tape W48/75mm alternative          Machine weight 85kg</p>	<p>Wood case</p>




<p>GNB-56 Top and Bottom Belts Driven Carton Sealer</p>		<p>Model GNB-56            Production speed 0-20ctns/min            Carton size(mm) L150-∞xW180-500x            H150-600mm            Power supply 220/110V,1 φ ,50HZ            Power 240W            Adhesive tape width 48/60/75MM            Machine dimension            L1020xW850xH1450mm            Machine weight 130KG</p>	<p>Wood case</p>
<p>GNS-05 Top and bottom belts driven carton sealer</p>		<p>Model GNS-05            Production speed 0-20ctns/min            Carton size(mm) L150-∞xW250- 500x            H90-450mm            Power supply 220/110V、1 φ 、50HZ            Power 240W            Adhesive tape width 48/60/75MM            Machine dimension            L860xW930xH1250mm            Machine weight 150KG</p>	<p>Wood case</p>
<p>ZZFA-05 semi-automation carton sealer</p>		<p>Model ZZFA-05            Production speed 0-20ctns/min            Carton size(mm) L150-∞xW120-500x            H120-500mm            Power supply 220/380V,50HZ Power            0.2kW            Adhesive tape width 48/60/75MM            Machine dimension            L1000xW900xH1375mm            Machine weight 120KG</p>	<p>Wood case</p>
<p>ZZFB-05 semi-auto carton sealer</p>		<p>Model ZZFB-05            Production speed 0-20ctns/min            Carton size(mm) L150-∞xW180-500x            H120-500mm            Power supply 220/380V,50HZ            Power 0.2kW            Adhesive tape width 48/60/75MM            Machine dimension            L1000xW900xH1375mm            Machine weight 126KG</p>	<p>Wood case</p>



<p>ZZFC-05 semi- automation carton sealer</p>		<p>Model ZZFC-05 Production speed 0-20ctns/min Carton size(mm) L200-600xW120- 500x H120-500mm Power supply 220/380V,50HZ Power 0.2kW Adhesive tape width 48/60/75MM Machine dimension L1700xW900xH1510mm Machine weight 180KG Using gas source:6kgf/cm<sup>2</sup>、40nl/min</p>	<p>Wood case</p>
<p>ZZFI-05 Automatic Flaps Folding Carton Sealer</p>		<p>Min Carton Size L200 * W150* H150mm Max Carton Size L600 *W500 *H500mm Sealing speed :20 m / min Mechanical Dimensions: L1700 * W840 * H1450mm (in actual size) Power supply: 220V 50Hz single phase/380v 3-phasig Power consumption: Max0.2KW For tape: W48, 60 75 alternative Machine weight: about 280KG</p>	<p>Wood case</p>
<p>ZZFG-05L L Corner and Side Type Carton Sealer</p>		<p>Min carton size: L320 * W200* H200mm Max carton size: L500 *W500 * H500mm Sealing speed :6-10 boxes / min Mechanical Dimensions: 2100L * W1250 * H1500mm (in actual size) Power supply: 220V 50Hz single phase Power consumption: Max 1.0KW For tape: W48, 60 alternative Machine weight: about 440KG</p>	<p>Wood case</p>



<p>ZZFP-05A carton sealing mahcine</p>		<p>Min carton size: L150 * W120* H120mm            Max carton size: L ∞ * W500 *H500mm            Sealing speed: 20 m / min            Mechanical Dimensions: 1300L *            W900 * H1375mm (in actual size)            Power supply: 220V 50Hz single phase            Power consumption: Max 0.4KW            For tape: W48, 60 alternative            Machine weight: about 130KG            Applicable Description: Deal packer            job manually adjust the width,height,            extended on both sides ofthe belt drive            Desktop drum: diameter 32mm,            aluminum alloy            Landing mode: Casters</p>	<p>Wood case</p>
<p>ZZFA-05P semi-autic carton sealer</p>		<p>Min carton size: L150 *W180*H150mm            Max carton size: L ∞ * W500 *H500mm            Sealing speed: 20 m / min            Mechanical Dimensions: 1000L *W900 *            H1375mm (in actual size)            Power supply: 220V 50Hz single phase            Power consumption: Max 0.3KW            For tape: W48, 60 alternative            Machine weight: about 130KG            Applicable Description: Suitable for            a wide, heavy-duty cardboard boxes,            manually adjust the width, height and            lower sides plus top drive            Desktop drum: diameter 32mm,            aluminum alloy            Landing mode: Casters</p>	<p>Wood case</p>



<p>ZZFE-05 Autic carton sealer</p>		<p>Min carton size: L150 * W160* H120mm            Max carton size: L ∞ * W500 *H500mm            Sealing speed: 20 m / min            Mechanical Dimensions: 1160L * W880 * H1245mm (in actual size)            Power supply: 220V 50Hz single phase            Power consumption: Max 0.2KW            For tape: W48, 60 alternative            Machine weight: about 170KG            Applicable Description:            Simultaneous multi-standard cartons, automatically adjust the width, height and lower sides of the belt drive            Desktop drum: diameter 32mm, aluminum alloy            Landing mode: Casters</p>	<p>Wood case</p>
<p>ZZFH-05 Full- autic Corner and Side Type Carton Sealer</p>		<p>Minimum Carton Size: L320 * W200* H200mm            Maximum Carton Size: L500 *W500 * H500mm            Sealing speed :6-10 boxes / min            Mechanical Dimensions: 2110L *W1250 * H1500mm (in actual size            Power supply: 220V 50Hz single phase            Power consumption: Max 1.0KW            For tape: W48, 60 alternative            Machine weight: about 480KG            Applicable Description: Includes 90-degree turn to push boxes institutions, automatic adjust the width, height, front-end sealing machine to be supporting a font            Landing mode: Casters</p>	<p>Wood case</p>
<p>ZZFG-05L+ZZFA-05 Full- autic carton sealing machine</p>		<p>Minimum Carton Size: L320 * W200* H200mm            Maximum Carton Size: L500 *W500 * H500mm            Sealing speed :6-10 boxes / min            Machine size: L1000 * W900 *H1375 + 2110 L * W1250 *H1500mm            Power supply: 220V 50Hz single phase            Power consumption: Max 1.2KW            For tape: W48, 60 alternative            Landing mode: Casters</p>	<p>Wood case</p>

<p>ZZFG-05L+ZZFC-05 Full-automatic carton sealing machine</p>		<p>Min carton size: L320 * W200* H200mm Max carton size: L500 *W500 * H500mm Sealing speed :6-10 boxes / min Machine size: L1700 * W900 *H1510 +2110 L * W1250 *H1500mm Power supply: 220V 50Hz single phase Power consumption: Max 1.4KW For tape: W48, 60 alternative</p>	<p>Wood case</p>
<p>GNA-05P automation carton sealer</p>		<p>Landing mode: Casters Model GNA-05P Conveyor speed 0-20m/min Max package L ∞ ×W500 × H500mm Min package L150 ×W150 ×H120mm Power supply 220/380V 50Hz Consumption Function 360W Dimension L1020 × W900 × H1350 (excluding before Roller Frame) For tape W48mm/60mm/75mm(alternative use) Machine weight 140kg</p>	<p>Wood case</p>
<p>GNE-05 Automatic Side Belts Driven Carton Sealer</p>		<p>Model GNE-05 Production speed 0-20ctns/min Carton size(mm) L150-∞xW150-500x H140-500mm Power supply 220/110V、1 φ、50HZ Power 240W Adhesive tape width 48/60/75MM Machine dimension L1170xW900xH1350mm Machine weight 170KG</p>	<p>Wood case</p>
<p><b>Case erector series</b></p>			



<p>GNK-40 Automatic Carton Erector</p>		<p>Model GNK-40 Production speed 12ctns/min Power supply 110V/220V、1 φ、 50-60HZ 200W Carton size(mm) L250-450xW150-400x H100-400 Air compressing 6kg/cm<sup>3</sup> Air consumption 450NL/MIN Machine dimension L2000xW1900xH1450mm Machine weight 450KG Adhesive tape width 48/60/75MM</p>	<p>Wood case</p>
<p>GNK-40A Automaticly Carton Bottom sealing Machine</p>		<p>Model GNK-40A Production speed 8ctns/min Power supply 110V/220-240V、1 φ、 50-60HZ 200W Carton size(mm) L200-500xW150- 400xH100-600 Power supply 110V/220-240V、1 φ 50-60HZ Power 200W Adhesive tape width W48mm、60mm、 75mm Machine dimension L1780xW850xH800mm Machine weight 250KG</p>	<p>Wood case</p>
<p>GNK-50 Automatic Carton Erector</p>		<p>Carton L200-500 W150-500 H100-500 Table height 650mm Sealing speed 600-720 boxes / hour Mechanical Dimensions L2000 × W1800 × H1200mm Power supply 220/380V 50/60Hz For tape 48-75mm alternative use Using gas source 5kg/cm<sup>3</sup> Machine weight 350kg Low-desktop</p>	<p>Wood case</p>





<p>ZZFK-05 Autic carton erector</p>		<p>Min carton size: L200 * W200 * H100mm            Max carton size: L450 *W400 * H400mm            Sealing speed :0-10 boxes / min            Mechanical Dimensions: 2150L W1900 * H1450mm (in actual size)            Power supply: 220V 50Hz single phase            Power consumption: Max 0.4KW            For tape: W48, 60 alternative            Machine weight: about 400KG            Applicable Description: Vertical box, cylinder shaped body, constant speed            Landing mode: Foot Cup</p>	<p>Wood case</p>
<p>GNK-40H18 Automatic Carton Erector</p>		<p>Technical Parameter:            Model GNK-40H18            Production speed 18ctns/min            Power supply 110V/220V、1 φ、50-60HZ 200W            Carton size(mm) L250-400xW150-350x H100-350            Air compressing 6kg/cm<sup>3</sup>            Air comsumption 450NL/MIN            Machine dimension L2000xW1900xH1450mm            Machine weight 550KG            Adhesive tape width 48/60/75MM</p>	<p>Wood case</p>
<p><b>Shrink packing machine series</b></p>			


<p>N-2000 stretch wrapping machine</p>		<p>Wrapping Specification 500-1200× 500-1200 mm          Turntable size φ1500          PackageHeight1800(2000/2200/2400m optional)          Packaging efficiency 20-40 Torr / hour          Turntable speed 0-12rpm speed frequency adjustable turntable slowstart / slow stop          Turntable height 85mm height from the ground          Turntable bearing (max) 2000kg          Membrane barrier stretch film frame rack system that allows Wrapping closer, automatic film feeding DC drive system Lifting column double chain structure, vertical speed adjustable frequency;          Control system PLC control, number of layers, the number of adjustable height and turntable auto-sensing automatic reset;          Weight 750kg</p>	<p>Wood case</p>
<p>G-2002 stretch wrapping machine</p>		<p>Turntable diameter 1500mm          Effective packing height 2100mm          Turntable bearing 2000kg          Packaging efficiency 20-40 Torr /hour          Turntable speed 0-15rpm, frequency adjustable speed, slow dial slow stop          Turntable height 82mm          Film frame rate 3m/min          Control system PLC control          Work auto / manual interchangeable          Power / Power 1PH220VAC,50/60Hz, 20A,1.15kw          Dimensions 2565 * 1500 * 2535          Weight 680kg</p>	<p>Wood case</p>



<p>G-XL02 Baggage wrapping machine</p>		<p>Wrapping size L (400-1000) W (180-600) H (300-850) mm Turntable speed 25rpm Turntable bearing 110kg System power pre-stretch film frame Film frame rate 3m/min Power / Power 1PH 220VAC, 50Hz, 20A, 1.0kw Dimension L1625 * W650 * H1480mm Weight 220kg.</p>	<p>Wood case</p>
<p>G-ZR02 worker stretch warpping machine</p>		<p>Control systems:PLC Suitable length and width of the largest packaging limited, standard height 2100mm(can be customized 2500mm) Applicable minimum packaging L600 * W600 * H700mm For cargo weight more than 100KG Applicable Stretch Core Diameter 75mm 250mm diameter for Stretch Single-phase charging power supply 220V/50HZ</p>	<p>Wood case</p>
<p>G-2002RY pallet Pre-LAC pressure wrapper</p>		<p>Wrapping Specification (500-1200) × (500-1200) mm Turntable size φ1500 Turntable height 85mm from the ground Package Height 2100mm Packaging efficiency 20-40 Torr /hour Turntable speed 0-12rpm speed frequency adjustable turntable slow start / slow stop Turntable bearing (max) 2000kg Film pre-stretch film carriage rack system, the proportion of pre-stretch up to 250%, automatic film feeding DC drive system Lifting column double chain structure, vertical speed adjustable frequency; Control system PLC control, number of layers, the number of adjustable height and turntable auto-sensing automatic reset Weight 750kg</p>	<p>Wood case</p>

<p>G-2002R pallet Pre-LAC wrapper</p>		<p>Turntable diameter 1500mm optional 1650mm, 1800mm Effective packing height 2100mm, optional 2400mm, 2600mm Turntable bearing 2000kg Packaging efficiency 20-40 Torr /hour Turntable speed 0-15rpm, frequency adjustable speed, slow dial slow stop Turntable height 82mm Film frame rate 3m/min 20kg adjustable pressure pressure top Working pressure 0.4-0.7Mpa Cylinder stroke 800mm Control system PLC control Work auto / manual interchangeable Power / Power 1PH220VAC, 50/60Hz,20A,1.35kw Dimensions 2565 * 1500 * 2535MM Weight 730kg</p>	<p>Wood case</p>
<p>N-2000RY stretch wrapping machine</p>		<p>Wrapping Specification (500-1200) mm × (500-1200) mm Turntable size φ1500/φ1650/φ 1800mm/φ2000mm (optional) Turntable height 85mm from the ground Package Height 1800mm (2000mm/2200mm/2400mm optional) Top pressure stroke 800mm/1000mm/1200mm (optional) Packaging efficiency 20-40 Torr /hour Turntable speed 0-12rpm speed frequency adjustable turntable slow start / slow stop Turntable bearing (max) 2000kg Film pre-stretch film carriage rack system, the proportion of pre-stretch up to 250%, automatic film feeding DC drive system</p>	<p>Wood case</p>

<p>G-2002R pallet Pre-LAC wrapper</p>		<p>Turntable diameter 1500mm optional 1650mm, 1800mm Effective packing height 2100mm, optional 2400mm, 2600mm Turntable bearing 2000kg Packaging efficiency 20-40 Torr /hour Turntable speed 0-15rpm, frequency adjustable speed, slow dial slow stop Turntable height 82mm Film frame rate 3m/min 20kg adjustable pressure pressure top Working pressure 0.4-0.7Mpa Cylinder stroke 800mm Control system PLC control Work auto / manual interchangeable Power / Power 1PH220VAC, 50/60Hz,20A,1.35kw Dimensions 2565 * 1500 * 2535MM Weight 730kg</p>	<p>Wood case</p>
<p>N-2000RY</p>		<p>Wrapping Specification (500-1200) × (500-1200) mm Turntable size φ1500/φ1650/φ 1800mm/φ2000mm (optional) Turntable height 85mm height from the ground Package Height 1800mm (2000mm/2200mm/2400mm optional) Top pressure stroke 800mm/1000mm/1200mm (optional) Packaging efficiency 20-40 Torr /hour Turntable speed 0-12rpm speed frequency adjustable turntable slowstart / slow stop Turntable bearing (max) 2000kg Film pre-stretch film carriage rack system, the proportion of pre-stretch up to 250%, automatic film feeding DC drive system</p>	<p>Wood case</p>



<p>G-AUTO- 02 Automatic stretch wrapping machine</p>		<p>Wheel diameter:1650mm or 1800mm The effective packing height 2100mm, orl 2400mm, 2600mm Turntable bearing 2000kg The packing efficiency Torr / h 20-30 Rotary speed 0-15rpm, ariable frequency adjustable speed, rotary corrosion corrosion stop Table height 136mm Working pressure 0.4-0.7Mpa The top film mechanism of lifting speed 3m/min The top film drawing mechanism of film speed 12m/min The top film size width 1700mm, length adjustable The film frame lifting speed 3m/min The control system of PLC control Remote control work Power /power3PH380VAC, 50/60Hz, 20A, 3kw <b>Dimensions of 2960* 2625* 3100MM</b></p>	<p>Wood case</p>
<p>N-2000RM wrapping machine machine</p>		<p>Wrapping Size L (500-1200) mm × W (500-1200) mm Turntable size φ1650 Turntable height 95mm height from the ground Package Height 1800mm Packaging efficiency 20-40 Torr /hour Turntable speed 0-12rpm speed frequency adjustable turntable slow start / slow stop Turntable bearing (max) 900kg or less Film pre-stretch film carriage rack system, the proportion of pre-stretch up to 250%, automatic film feeding DC drive system Lifting column double chain structure, vertical speed adjustable frequency Control system PLC control, number of layers, the number of adjustable height and turntable auto-sensing automatic reset Weight 750kg</p>	<p>Wood case</p>

<p>N-600F stretch wrapping machine</p>		<p>1 Dimension: 1350 * 600 * 1940mm (at actual size based)                  2 Wrapping size: L600 * W600 * H350-400mm                  3 Packaging efficiency :20-40 / hour                  4 wheel height :550-600mm                  5 turntable bearing: 100kg                  6 top pressure device: mechanical pressure arm, safe and stable                  7 Total power: 0.55kw                  8 Power supply voltage: 220V (single phase)                  9 Turntable speed: 0 to 12 rev / min                  10 Weight: 260kg</p>	<p>Wood case</p>
<p>N-2000R pallet Pre-LAC stretch wrapper</p>		<p>Wrapping Specification (500-1200)mm × (500-1200) mm                  Turntable size φ1500                  Turntable height 85mm height from the ground                  Package Height 1800mm                  Packaging efficiency 20-40 Torr /hour                  Turntable speed 0-12rpm speed frequency adjustable turntable slow start / slow stop                  Turntable bearing (max) 2000kg                  Film pre-stretch film carriage racksystem, the proportion of pre-stretch up to 250%, automatic film feeding DC drive system                  Lifting column double chain structure, vertical speed adjustable frequency;                  Control system PLC control, number of layers, the number of adjustable height and turntable auto-sensing automatic reset                  Weight 750kg</p>	<p>Wood case</p>
<p><b>Cigarette case film wrapping machine</b></p>			

<p>SX-200 film wrapping machine for cigarette box and Cosmetic box</p>		<p>Model: SX-200            Packaging materials: BOPP cigarette film (with optional gold wire)            Packing speed: 15 to 30 bags / min            Max packing size: L (40-200) × W(30-100) × H (10-80) mm            Weight: 180kg            Power supply: 220V            Using gas source: 5KG            Machine size: L1200 * W700 *900mm</p>	<p>Wood case</p>
<p>SX-300 film wrapping machine for cigarette box and Cosmetic box</p>		<p>Model: SX-300            Packaging materials: BOPP cigarette film (with optional gold wire)            Packing speed: 15 to 30 bags / min            Max packing size L (80-300) × W(50-200)× H (20-100) mm            Weight: 230kg            Power supply: 220V            Using gas source: 5KG            Machine size: L1400 * W900 *1000mm</p>	<p>Wood case</p>
<p>S-300A full-auto film wrapping machine for cigarette box and Cosmetic box</p>		<p>Model: S-300A            Packaging materials: BOPP cigarette film (with optional gold wire)            Packing speed :40 to 80 packs / min            Max packing size :L 240 × W120 × H 60mm            Power and total power: 220V 50Hz5kw            Machine weight :500kg            Machine dimensions :L 2000 ×W700× H1400mm</p>	<p>Wood case</p>
<p><b>Shrink packing machine series</b></p>			
<p>GNS-4525L Shrinking machine</p>		<p>Power Supply:220/380V 50/60Hz 3P            Heater power:13kw            Heater power:10Kg            Working speed:0-12M/min            Tunnel size:L1200×W450×H250mm            Machine size:L1600×W715×H1520mm            Machine Weight:200kg</p>	<p>Wood case</p>

<p>GNL-5545T Manual L-sealing machine</p>		<p>Model GNL-5545T Power supply 110/220V 1.2kw 50/60Hz Packing size L450×W400×H250mm Current size L550×W450mm Packing speed 800-1000pcs/h Machine dimension L1600×W775×H1000mm Machine weight 130kg High temperature and sticky free L bar sealing knife, sealing action without smoke and burn The seal is tidy and clean. Telfon covered on the sealing knife. Sealing time is accurately controlled by time delay</p>	<p>Wood case</p>
<p>GNS-5030 Automatic shrinking tunnel</p>		<p>Max. packing size L700*W400*H200 (customizable for case size out of range) Stainless steel version Table height adjustable Interchangeable direction of machine per product feeding Machine body color is optional Bespoke plug apply to different area In-feed and out-feed conveyor is available Power: 110VAC, 380VAC, single phase, 3 phase Guiding pole device on conveyor is available Movable independent electric box control system Pressure device for flat and light product like book Teflon conveyor or stainless steel conveyor Combined with side sealing machine GNL-5545C</p>	<p>Wood case</p>
<p>GNS-5030LW Automatic Shrinking Tunnel</p>		<p>Model GNS-5030LW Power supply 380V、3φ、50-60Hz Power 16kw Packing speed L1200×W450×H250mm highest temperature 250°C Turnl size L1500×W500×H300mm Machine dimension L2000×W1100×H1250mm Machine weight 650kg</p>	<p>Wood case</p>

<p>GNL-5545C L-bar sealing machine</p>		<p>Power 3 &amp; 380V 50/60Hz ≤ 3kw          Good size L infinitely          wide 300mm high 150mm          Many punch punch to the contraction of the air bag can be quickly discharged          Body parts material carbon steel, the key parts made of stainless steel and aluminum production, ensuring solid structure          Mechine Dimensions 1650 * 900 * 1550mm          Packing speed ranges depending on the package size (0-30 pcs / min)          Pressure 5.5KG/cm2</p>	<p>Wood case</p>
<p>GNL-4535 L-bar sealing machine</p>		<p>Power supply 220V、1 φ、50-60Hz          Packing size L+H≤500mm/ (H≤100mm)          Product W+H /tunnel size L550×W450mm          Packing speed 1-25pcs/min          Air compressing 5.5kg/cm³          Max current 10A          Net weight 250kg          Machine dimension L1830×W850×H1550mm</p>	<p>Wood case</p>
<p>GNS-4525 Shrinking machine</p>		<p>Power Supply:220/380V 50/60Hz 3P          Heater power:10kw          Heater power:10Kg          Working speed:0-12M/min          Tunnel size:L1000×W450×H250mm          Machine size:L1300×W715×H1455mm          Machine Weight:185kg</p>	<p>Wood case</p>
<p><b>Flap carton sealer series (hot melt glue)</b></p>			



<p>GN-F02 Two Flap carton sealer (hot melt glue)</p>		<p>Type:GN-F02 Capacity:57 boxes / min Total Power:0.37kw+1.6kw Electrical:AC220V 50HZ Net Weight:250kg Eternal Dimension:2100*910*1300mm APPLICable size:L100-320*W40-250*H25-100mm Materials: Hot melt adhesive</p>	<p>Wood case</p>
<p>GN-F01 Semi-automaiton Single Flap carton sealer (hot melt glue)</p>		<p>Sealing speed 10 boxes /min Power supply 220v The size range for paper L80-300 × W44-200 × H25-80mm</p>	<p>Wood case</p>
<p>GN-F03 Automation Two Flap carton sealer (hot melt glue)</p>		<p>Sealing speed: 47 boxes / min Power supply: AC220 50HZ Total power: 1.97KW Vertebral sub-interval: 380mm Applicable carton size range: length:100-210mm Width :40-250 high:25-80mm Dimensions: L1200 * W910 *H1000mm Custom designed for the amount of small business, the machine can work 24 hours, the failure rate is very low, all 304 stainless steel will never rust;</p>	<p>Wood case</p>