

# PRODUCTS      CATALOGUE

Strapping tool series

Strapping machine series

Case sealer series

Case erector series

Transparent film three-dimensional packing machine series

Stretch wrapper series

Shrink packing machine series

Flap carton sealer series (hot melt glue)




**Strapping tool series**




| Product Name                            | PICTURE   | TECHNICAL SPECIFICATIONS   | PACKAGING |
|---|---|--|-----------|
| A6 PP/PET pneumaticl strapping tool     |    | A4 for the bandwidth 9.5-16mm<br>A6 for the bandwidth 13-19mm<br>A8 for the bandwidth 19-25mm<br>Applied with a thickness 0.4-1.5mm<br>Machine Rally 3200N<br>Frictional heat welding connection<br>Air pressure 5.0-7.0kg/cm <sup>3</sup><br>Machine size 275 × 115 × 113mm<br>Weight 3.9kg | Carton    |
| ZP92 battery powered PET strapping tool |   | Weight 2.9kgs<br>Max tension 250kgs<br>Applicable Material PET / PP<br>For Bandwidth 9-16mm<br>Applicable generous 0.55-1.35mm<br>Packing efficiency of 300 -500<br>Charging time 30 minutes<br>Power Source 18V 3000mAh lithium battery   | Carton    |
| ZP96 battery powered PET strapping tool |  | Weight 2.9kgs<br>Max tension 400kgs<br>Applicable Material PET / PP<br>For the bandwidth 16-19mm<br>Applicable generous 0.55-1.35mm<br>Packing efficiency of 300 -500<br>Charging time 30 minutes<br>Power Source 18V 3000mAh lithium battery  | Carton    |
| P322 battery powered PET strapping tool |  | Applied with a thickness 0.4-1.05mm<br>For the bandwidth 10-16mm<br>Frictional heat welding connection<br>Tightening tension 2400N<br>Weight 4.3kg   | Carton    |





|   |   |   |               |
|---|---|---|---------------|
| <p>GND16&amp;19<br/>pneumatic steel<br/>strapping<br/>handle<br/>tool</p> |    | <p>Model GN-16 &amp; GN-19<br/>Brand Origin GUONUO<br/>For the bandwidth 16-19mm(choose )<br/>Applied with a thickness 0.38-0.63mm<br/>Tightening tension 4500N<br/>Connection single bite buckle<br/>Weight 4.6kg (including jib) 10</p> | <p>Carton</p> |
| <p>GN25&amp;32气<br/>pneumatic steel<br/>strapping<br/>handle<br/>tool</p> |    | <p>Model GN-32<br/>Brand Origin China<br/>Apply pressure 0.42 - 0.6Mpa<br/>Applied with a thickness 0.8-1.0mm<br/>For the bandwidth 25-32mm<br/>Maximum tension 7000N<br/>Rally jaws 9000N</p>  | <p>Carton</p> |
| <p>MH35 steel<br/>strapping<br/>handle<br/>tool</p>                       |   | <p>Model MH-35<br/>Origin Taiwan<br/>For the bandwidth 16-19mm<br/>Applied with a thickness 0.55-<br/>0.75mm<br/>Connection yin and yang buckle<br/>(buckle-free)<br/>Max tension 8000N<br/>Weight 4.2kg</p>                              | <p>Carton</p> |
| <p>MH32 steel<br/>strapping<br/>handle<br/>tool</p>                       |  | <p>Model MH-32<br/>For the bandwidth 13-19mm<br/>Applied with a thickness 0.38-0.63mm<br/>Connection yin and yang buckle<br/>(buckle-free) Manual operation<br/>Weight 3.7kg</p>  | <p>Carton</p> |

|  |   |  |                  |
|--|---|--|------------------|
| <p>LY-32<br/>pneumatic<br/>steel strapping<br/>handle tool</p> |    | <p>Pneumatic strapping locking device<br/>Model LY-19 &amp; 25 &amp; 32<br/>Air pressure 0.45-0.6Mpa<br/>Steel specification (25-32) ×(0.8-1.2)mm<br/>Lock buckle form<br/>Lock part of tensile strength ≥16.8KN<br/>Weight 3.2kg<br/>Strapping Material Steel<br/>Pneumatic strapping tensioner<br/>Air pressure 0.4-0.6Mpa<br/>steel specification (25-32) × (0.8-1.2)mm<br/>Strip tension speed 5m/min<br/>Tensioning ≥ 9.8KN/0.6Mpa<br/>Weight 4.3kg</p> | <p>Carton</p>    |
| <p><b>Strapping machine series</b></p>                         |   |  |                  |
| <p>D53 Semi-Automatic Strapping Machine</p>                    |   | <p>Power 220V/110V/50HZ/1 phase<br/>Power 0.66KW<br/>Maximum contraction force 60kg<br/>PP width 6-15mm<br/>Minimum packing material 60mm<br/>Maximum packing material limitation<br/>Strapping Speed 1.5 seconds /section<br/>PP tape paper core diameter<br/>200mm/230mm/280mm<br/>Machine size L895 × W565 × H720-870mm<br/>Machine weight 85kg</p>   | <p>Wood case</p> |
| <p>D-301B Full-atic Low-mesa Strapping Machine</p>             |  | <p>Power 380V/50HZ<br/>Machine power 1600W<br/>Strapping speed 2.0Sec./Strap<br/>Maximum force tied tight 80kg<br/>For PP with a wide 9-15mm<br/>thick 0.5-1.0mm<br/>Bow Frame Size W850 × H600mm<br/>Machine Size L1880 * W600* H1200mm<br/>Machine weight 280kg</p>  | <p>Wood case</p> |

|  |   |   |                  |
|--|---|---|------------------|
| <p>D-103C<br/>Automatic<br/>Strapping<br/>Machine</p>          |    | <p>Power 220V/50Hz<br/>Power 0.66kw<br/>Maximum contraction force 60kgs<br/>PP tape paper core 200mm<br/>Weight 80kgs</p>   | <p>Wood case</p> |
| <p>D53L semi-<br/>automatic PP<br/>strapping<br/>machine</p>   |    | <p>Model D53L<br/>Power supply 380V<br/>50Hz220v/110v/50hz/1 phase<br/>Machine power 0.66KW<br/>Strapping speed 1.5Sec./Strap<br/>Minimum packing material :6-15mm<br/>Maximum packing material: Open<br/>Applicable PP width 6-15mm<br/>PP tape paper core diameter:<br/>200mm/230mm/280mm<br/>Machine weight 85kg</p> | <p>Wood case</p> |
| <p>WK02-30 paper<br/>and film tape<br/>banding<br/>machine</p> |  | <p>Applicable tape paper &amp; OPP tape<br/>Strapping width 30mm<br/>Maximum bundle size 410*200mm<br/>Minimum size 30*5mm strapping<br/>within the core size 40mm<br/>Strapping speed 1560/hour<br/>Strapping tension 5-40N<br/>Machine dimension 560 x 446 x1138mm<br/>Net weight 71kg</p>                            | <p>Wood case</p> |



|   |   |   |                  |
|---|---|---|------------------|
| <p>WK01-30 paper and film tape banding machine</p>      |    | <p>Model WK01-30<br/> Machine size 590 × 350 × 510mm(body)<br/> Machine's weight about 35kg<br/> Tied tight packing maximum force 40N<br/> Maximum package size W 380*H200mm<br/> Minimum package size W40 × H 40 mm<br/> Use material OPP and paper tape<br/> Packaging capacity of 400 bags/hour<br/> Thermal fusion bonding mode mode (using a special bonding method,beautiful solid)<br/> Strapping speed 2 seconds /second<br/> Packaged with dimensions 30mm<br/> Power 0.08KW</p> | <p>Wood case</p> |
| <p>D-301C side automatic strapping machine</p>          |   | <p>Model D-301C<br/> Power supply 220/380V 50/60Hz<br/> Machine power 850W<br/> Strapping speed 2sec/strap<br/> Tied tight power 5-80kg<br/> Applicable PP tape width 9-16mm thick 0.5-1.0mm<br/> Bow Frame Size W600 × H1450mm<br/> Dimension L1610 × W625 × H1840mm<br/> Machine weight 255kg</p>   | <p>Wood case</p> |
| <p>D-310C low-tabletape automatic strapping machine</p> |  | <p>Model D-310C<br/> Use the power 3PH-220V/380V 50/60Hz<br/> Machine power 850W<br/> Strapping speed 2sec/strap<br/> Tied tight power 5-80kg<br/> Applicable PP tape width 9-16mm thick 0.5-1.0mm<br/> Bow Frame Size W850 × H600mm<br/> Dimension L1880 × W600 × H1200mm<br/> Machine weight 280kg<br/> Table height 450mm</p>  | <p>Wood case</p> |




|   |   |  |                  |
|---|---|--|------------------|
| <p>D-301B side automation strapping machine</p> |    | <p>Model D-301B<br/>Use the power 380V/50HZ<br/>Machine power 1600W<br/>Strapping speed 2.0Sec./Strap<br/>Maximum force tied tight 80kg<br/>Applicable PP tape width 9-15mm thick 0.5-1.0mm<br/>Bow Frame Size W850 × H600mm<br/>Dimension L1880 × W600 × H1200<br/>Machine weight 280kg</p>   | <p>Wood case</p> |
| <p>D-102 automation strapping machine</p>       |   | <p>Power: 380V/50Hz 750W/5A (220V to be customized)<br/>Packing speed ≤ 2.5 sec / channel<br/>Table height 750mm<br/>Frame size width 800mm * height customized according to needs<br/>Packing type 1 multi-channel parallel, a little way, manual, and even hit the ball switch, foot switch<br/>Application package with thick (0.55~1.2) mm * Width (9 ~ 15) mm (actual customized by the user)</p> | <p>Wood case</p> |
| <p><b>Case sealer series</b></p>                |   |  |                  |
| <p>GNA -05 Automatic sealing machine</p>        |  | <p>The machine model GNA-05<br/>Conveyor speed 700-1200pcs/h<br/>Maximum size of package L ∞ x W500 x H500mm<br/>The minimum package size L150 x W100 x H100mm<br/>The power supply for 110V/220V 50/60Hz<br/>machine size L1020* W850*H1350mm<br/>Applicable tape W48/75mm alternative<br/>Machine weight 85kg</p>  | <p>Wood case</p> |




|   |   |  |                  |
|---|---|--|------------------|
| <p>GNB-56 Top and Bottom Belts Driven Carton Sealer</p> |    | <p>Model GNB-56<br/>         Production speed 0-20ctns/min<br/>         Carton size(mm) L150-∞xW180-500x<br/>         H150-600mm<br/>         Power supply 220/110V,1 φ ,50HZ<br/>         Power 240W<br/>         Adhesive tape width 48/60/75MM<br/>         Machine dimension<br/>         L1020xW850xH1450mm<br/>         Machine weight 130KG</p> | <p>Wood case</p> |
| <p>GNS-05 Top and bottom belts driven carton sealer</p> |    | <p>Model GNS-05<br/>         Production speed 0-20ctns/min<br/>         Carton size(mm) L150-∞xW250- 500x<br/>         H90-450mm<br/>         Power supply 220/110V、1 φ 、50HZ<br/>         Power 240W<br/>         Adhesive tape width 48/60/75MM<br/>         Machine dimension<br/>         L860xW930xH1250mm<br/>         Machine weight 150KG</p>  | <p>Wood case</p> |
| <p>ZZFA-05 semi-automation carton sealer</p>            |  | <p>Model ZZFA-05<br/>         Production speed 0-20ctns/min<br/>         Carton size(mm) L150-∞xW120-500x<br/>         H120-500mm<br/>         Power supply 220/380V,50HZ Power<br/>         0.2kW<br/>         Adhesive tape width 48/60/75MM<br/>         Machine dimension<br/>         L1000xW900xH1375mm<br/>         Machine weight 120KG</p>    | <p>Wood case</p> |
| <p>ZZFB-05 semi-auto carton sealer</p>                  |  | <p>Model ZZFB-05<br/>         Production speed 0-20ctns/min<br/>         Carton size(mm) L150-∞xW180-500x<br/>         H120-500mm<br/>         Power supply 220/380V,50HZ<br/>         Power 0.2kW<br/>         Adhesive tape width 48/60/75MM<br/>         Machine dimension<br/>         L1000xW900xH1375mm<br/>         Machine weight 126KG</p>    | <p>Wood case</p> |





|  |   |  |                  |
|--|---|--|------------------|
| <p>ZZFC-05<br/>semi-<br/>automation<br/>carton sealer</p>        |    | <p>Model ZZFC-05<br/>Production speed 0-20ctns/min<br/>Carton size(mm) L200-600xW120- 500x<br/>H120-500mm<br/>Power supply 220/380V,50HZ<br/>Power 0.2kW<br/>Adhesive tape width 48/60/75MM<br/>Machine dimension<br/>L1700xW900xH1510mm<br/>Machine weight 180KG<br/>Using gas source:6kgf/cm<sup>2</sup>、40nl/min</p>                                | <p>Wood case</p> |
| <p>ZZFI-05<br/>Automatic Flaps<br/>Folding Carton<br/>Sealer</p> |   | <p>Min Carton Size L200 * W150* H150mm<br/>Max Carton Size L600 *W500 *H500mm<br/>Sealing speed :20 m / min<br/>Mechanical Dimensions: L1700 *<br/>W840 * H1450mm (in actual size)<br/>Power supply: 220V 50Hz single<br/>phase/380v 3-phasig<br/>Power consumption: Max0.2KW<br/>For tape: W48, 60 75 alternative<br/>Machine weight: about 280KG</p> | <p>Wood case</p> |
| <p>ZZFG-05L L<br/>Corner and Side<br/>Type Carton<br/>Sealer</p> |  | <p>Min carton size: L320 * W200* H200mm<br/>Max carton size: L500 *W500 *<br/>H500mm<br/>Sealing speed :6-10 boxes / min<br/>Mechanical Dimensions: 2100L *<br/>W1250 * H1500mm (in actual size)<br/>Power supply: 220V 50Hz single phase<br/>Power consumption: Max 1.0KW<br/>For tape: W48, 60 alternative<br/>Machine weight: about 440KG</p>       | <p>Wood case</p> |



|  |   |  |                  |
|--|---|--|------------------|
| <p>ZZFP-05A<br/>carton sealing<br/>mahcine</p>   |    | <p>Min carton size: L150 * W120* H120mm<br/> Max carton size: L ∞ * W500 *H500mm<br/> Sealing speed: 20 m / min<br/> Mechanical Dimensions: 1300L *<br/> W900 * H1375mm (in actual size)<br/> Power supply: 220V 50Hz single phase<br/> Power consumption: Max 0.4KW<br/> For tape: W48, 60 alternative<br/> Machine weight: about 130KG<br/> Applicable Description: Deal packer<br/> job manually adjust the width,height,<br/> extended on both sides ofthe belt drive<br/> Desktop drum: diameter 32mm,<br/> aluminum alloy<br/> Landing mode: Casters</p>                           | <p>Wood case</p> |
| <p>ZZFA-05P<br/>semi-autic<br/>carton sealer</p> |  | <p>Min carton size: L150 *W180*H150mm<br/> Max carton size: L ∞ * W500 *H500mm<br/> Sealing speed: 20 m / min<br/> Mechanical Dimensions: 1000L *W900 *<br/> H1375mm (in actual size)<br/> Power supply: 220V 50Hz single phase<br/> Power consumption: Max 0.3KW<br/> For tape: W48, 60 alternative<br/> Machine weight: about 130KG<br/> Applicable Description: Suitable for<br/> a wide, heavy-duty cardboard boxes,<br/> manually adjust the width, height and<br/> lower sides plus top drive<br/> Desktop drum: diameter 32mm,<br/> aluminum alloy<br/> Landing mode: Casters</p> | <p>Wood case</p> |

|   |   |   |                  |
|---|---|---|------------------|
| <p>ZZFE-05 Autic carton sealer</p>                            |    | <p>Min carton size: L150 * W160* H120mm<br/>           Max carton size: L ∞ * W500 *H500mm<br/>           Sealing speed: 20 m / min<br/>           Mechanical Dimensions: 1160L * W880 * H1245mm (in actual size)<br/>           Power supply: 220V 50Hz single phase<br/>           Power consumption: Max 0.2KW<br/>           For tape: W48, 60 alternative<br/>           Machine weight: about 170KG<br/>           Applicable Description:<br/>           Simultaneous multi-standard cartons, automatically adjust the width, height and lower sides of the belt drive<br/>           Desktop drum: diameter 32mm, aluminum alloy<br/>           Landing mode: Casters</p> | <p>Wood case</p> |
| <p>ZZFH-05 Full- autic Corner and Side Type Carton Sealer</p> |  | <p>Minimum Carton Size: L320 * W200* H200mm<br/>           Maximum Carton Size: L500 *W500 * H500mm<br/>           Sealing speed :6-10 boxes / min<br/>           Mechanical Dimensions: 2110L *W1250 * H1500mm (in actual size<br/>           Power supply: 220V 50Hz single phase<br/>           Power consumption: Max 1.0KW<br/>           For tape: W48, 60 alternative<br/>           Machine weight: about 480KG<br/>           Applicable Description: Includes 90-degree turn to push boxes institutions, automatic adjust the width, height, front-end sealing machine to be supporting a font<br/>           Landing mode: Casters</p>                                 | <p>Wood case</p> |
| <p>ZZFG-05L+ZZFA-05 Full- autic carton sealing machine</p>    |  | <p>Minimum Carton Size: L320 * W200* H200mm<br/>           Maximum Carton Size: L500 *W500 * H500mm<br/>           Sealing speed :6-10 boxes / min<br/>           Machine size: L1000 * W900 *H1375 + 2110 L * W1250 *H1500mm<br/>           Power supply: 220V 50Hz single phase<br/>           Power consumption: Max 1.2KW<br/>           For tape: W48, 60 alternative<br/>           Landing mode: Casters</p>   | <p>Wood case</p> |

|   |   |  |                  |
|---|---|--|------------------|
| <p>ZZFG-05L+ZZFC-05<br/>Full-automatic carton sealing machine</p> |    | <p>Min carton size: L320 * W200* H200mm<br/>Max carton size: L500 *W500 * H500mm<br/>Sealing speed :6-10 boxes / min<br/>Machine size: L1700 * W900 *H1510 +2110 L * W1250 *H1500mm<br/>Power supply: 220V 50Hz single phase<br/>Power consumption: Max 1.4KW<br/>For tape: W48, 60 alternative</p>  | <p>Wood case</p> |
| <p>GNA-05P<br/>automation carton sealer</p>                       |    | <p>Landing mode: Casters<br/>Model GNA-05P<br/>Conveyor speed 0-20m/min<br/>Max package L ∞ ×W500 × H500mm<br/>Min package L150 ×W150 ×H120mm<br/>Power supply 220/380V 50Hz<br/>Consumption Function 360W<br/>Dimension L1020 × W900 × H1350 (excluding before Roller Frame)<br/>For tape W48mm/60mm/75mm(alternative use)<br/>Machine weight 140kg</p> | <p>Wood case</p> |
| <p>GNE-05<br/>Automatic Side Belts Driven Carton Sealer</p>       |  | <p>Model GNE-05<br/>Production speed 0-20ctns/min<br/>Carton size(mm) L150-∞xW150-500x H140-500mm<br/>Power supply 220/110V、1 φ、50HZ<br/>Power 240W<br/>Adhesive tape width 48/60/75MM<br/>Machine dimension L1170xW900xH1350mm<br/>Machine weight 170KG</p>   | <p>Wood case</p> |
| <p><b>Case erector series</b></p>                                 |   |  |                  |



|  |   |  |                  |
|--|---|--|------------------|
| <p>GNK-40<br/>Automatic<br/>Carton<br/>Erector</p>                   |    | <p>Model GNK-40<br/>Production speed 12ctns/min<br/>Power supply 110V/220V、1 φ、<br/>50-60HZ 200W<br/>Carton size(mm) L250-450xW150-400x<br/>H100-400<br/>Air compressing 6kg/cm<sup>3</sup><br/>Air consumption 450NL/MIN<br/>Machine dimension<br/>L2000xW1900xH1450mm<br/>Machine weight 450KG<br/>Adhesive tape width 48/60/75MM</p>  | <p>Wood case</p> |
| <p>GNK-40A<br/>Automaticly<br/>Carton Bottom<br/>sealing Machine</p> |   | <p>Model GNK-40A<br/>Production speed 8ctns/min<br/>Power supply 110V/220-240V、1 φ、<br/>50-60HZ 200W<br/>Carton size(mm) L200-500xW150-<br/>400xH100-600 Power supply<br/>110V/220-240V、1 φ 50-60HZ Power<br/>200W<br/>Adhesive tape width W48mm、60mm、<br/>75mm<br/>Machine dimension<br/>L1780xW850xH800mm<br/>Machine weight 250KG</p> | <p>Wood case</p> |
| <p>GNK-50<br/>Automatic<br/>Carton<br/>Erector</p>                   |  | <p>Carton L200-500 W150-500 H100-500<br/>Table height 650mm<br/>Sealing speed 600-720 boxes / hour<br/>Mechanical Dimensions L2000 × W1800<br/>× H1200mm<br/>Power supply 220/380V 50/60Hz<br/>For tape 48-75mm alternative use<br/>Using gas source 5kg/cm<sup>3</sup><br/>Machine weight 350kg<br/>Low-desktop</p>                     | <p>Wood case</p> |



|   |  |  |                  |
|---|--|--|------------------|
| <p>ZZFK-05<br/>Autic carton<br/>erector</p>           |   | <p>Min carton size: L200 * W200 * H100mm<br/>           Max carton size: L450 *W400 * H400mm<br/>           Sealing speed :0-10 boxes / min<br/>           Mechanical Dimensions: 2150L W1900 * H1450mm (in actual size)<br/>           Power supply: 220V 50Hz single phase<br/>           Power consumption: Max 0.4KW<br/>           For tape: W48, 60 alternative<br/>           Machine weight: about 400KG<br/>           Applicable Description: Vertical box, cylinder shaped body, constant speed<br/>           Landing mode: Foot Cup</p> | <p>Wood case</p> |
| <p>GNK-40H18<br/>Automatic<br/>Carton<br/>Erector</p> |  | <p>Technical Parameter:<br/>           Model GNK-40H18<br/>           Production speed 18ctns/min<br/>           Power supply 110V/220V、1 φ、50-60HZ 200W<br/>           Carton size(mm) L250-400xW150-350x H100-350<br/>           Air compressing 6kg/cm<sup>3</sup><br/>           Air comsumption 450NL/MIN<br/>           Machine dimension L2000xW1900xH1450mm<br/>           Machine weight 550KG<br/>           Adhesive tape width 48/60/75MM</p>  | <p>Wood case</p> |
| <p><b>Shrink packing machine series</b></p>           |  |  |                  |


|  |   |  |                  |
|--|---|--|------------------|
| <p>N-2000 stretch wrapping machine</p> |    | <p>Wrapping Specification 500-1200× 500-1200 mm<br/>         Turntable size φ1500<br/>         PackageHeight1800(2000/2200/2400m optional)<br/>         Packaging efficiency 20-40 Torr / hour<br/>         Turntable speed 0-12rpm speed frequency adjustable turntable slowstart / slow stop<br/>         Turntable height 85mm height from the ground<br/>         Turntable bearing (max) 2000kg<br/>         Membrane barrier stretch film frame rack system that allows Wrapping closer, automatic film feeding DC drive system Lifting column double chain structure, vertical speed adjustable frequency;<br/>         Control system PLC control, number of layers, the number of adjustable height and turntable auto-sensing automatic reset;<br/>         Weight 750kg</p> | <p>Wood case</p> |
| <p>G-2002 stretch wrapping machine</p> |  | <p>Turntable diameter 1500mm<br/>         Effective packing height 2100mm<br/>         Turntable bearing 2000kg<br/>         Packaging efficiency 20-40 Torr /hour<br/>         Turntable speed 0-15rpm, frequency adjustable speed, slow dial slow stop<br/>         Turntable height 82mm<br/>         Film frame rate 3m/min<br/>         Control system PLC control<br/>         Work auto / manual interchangeable<br/>         Power / Power 1PH220VAC,50/60Hz, 20A,1.15kw<br/>         Dimensions 2565 * 1500 * 2535<br/>         Weight 680kg</p>  | <p>Wood case</p> |



|   |   |   |                  |
|---|---|---|------------------|
| <p>G-XL02<br/>Baggage<br/>wrapping<br/>machine</p>          |    | <p>Wrapping size L (400-1000) W (180-600) H (300-850) mm<br/>Turntable speed 25rpm<br/>Turntable bearing 110kg<br/>System power pre-stretch film frame<br/>Film frame rate 3m/min<br/>Power / Power 1PH 220VAC, 50Hz, 20A, 1.0kw<br/>Dimension L1625 * W650 * H1480mm<br/>Weight 220kg.</p>   | <p>Wood case</p> |
| <p>G-ZR02 worker<br/>stretch warpping<br/>machine</p>       |   | <p>Control systems:PLC<br/>Suitable length and width of the largest packaging limited, standard height 2100mm(can be customized 2500mm)<br/>Applicable minimum packaging L600 * W600 * H700mm<br/>For cargo weight more than 100KG<br/>Applicable Stretch Core Diameter 75mm<br/>250mm diameter for Stretch<br/>Single-phase charging power supply 220V/50HZ</p>  | <p>Wood case</p> |
| <p>G-2002RY<br/>pallet Pre-LAC<br/>pressure<br/>wrapper</p> |  | <p>Wrapping Specification (500-1200) × (500-1200) mm<br/>Turntable size φ1500<br/>Turntable height 85mm from the ground<br/>Package Height 2100mm<br/>Packaging efficiency 20-40 Torr /hour<br/>Turntable speed 0-12rpm speed frequency adjustable turntable slow start / slow stop<br/>Turntable bearing (max) 2000kg<br/>Film pre-stretch film carriage rack system, the proportion of pre-stretch up to 250%, automatic film feeding DC drive system<br/>Lifting column double chain structure, vertical speed adjustable frequency;<br/>Control system PLC control, number of layers, the number of adjustable height and turntable auto-sensing automatic reset<br/>Weight 750kg</p> | <p>Wood case</p> |



|  |   |   |                  |
|--|---|---|------------------|
| <p>G-2002R pallet Pre-LAC wrapper</p>    |    | <p>Turntable diameter 1500mm<br/>optional 1650mm, 1800mm<br/>Effective packing height 2100mm,<br/>optional 2400mm, 2600mm<br/>Turntable bearing 2000kg<br/>Packaging efficiency 20-40 Torr /hour<br/>Turntable speed 0-15rpm,<br/>frequency adjustable speed, slow dial<br/>slow stop<br/>Turntable height 82mm<br/>Film frame rate 3m/min<br/>20kg adjustable pressure pressure top<br/>Working pressure 0.4-0.7Mpa Cylinder<br/>stroke 800mm<br/>Control system PLC control<br/>Work auto / manual interchangeable<br/>Power / Power 1PH220VAC,<br/>50/60Hz,20A,1.35kw<br/>Dimensions 2565 * 1500 * 2535MM<br/>Weight 730kg</p> | <p>Wood case</p> |
| <p>N-2000RY stretch wrapping machine</p> |  | <p>Wrapping Specification (500-1200)<br/>mm × (500-1200) mm<br/>Turntable size φ1500/φ1650/φ<br/>1800mm/φ2000mm (optional)<br/>Turntable height 85mm from the ground<br/>Package Height 1800mm<br/>(2000mm/2200mm/2400mm optional)<br/>Top pressure stroke<br/>800mm/1000mm/1200mm (optional)<br/>Packaging efficiency 20-40 Torr /hour<br/>Turntable speed 0-12rpm speed<br/>frequency adjustable turntable slow<br/>start / slow stop<br/>Turntable bearing (max) 2000kg<br/>Film pre-stretch film carriage rack<br/>system, the proportion of pre-stretch<br/>up to 250%, automatic film feeding<br/>DC drive system</p>       | <p>Wood case</p> |

|   |   |  |                  |
|---|---|--|------------------|
| <p>G-2002R pallet<br/>Pre-LAC<br/>wrapper</p> |    | <p>Turntable diameter 1500mm<br/>optional 1650mm, 1800mm<br/>Effective packing height 2100mm,<br/>optional 2400mm, 2600mm<br/>Turntable bearing 2000kg<br/>Packaging efficiency 20-40 Torr /hour<br/>Turntable speed 0-15rpm,<br/>frequency adjustable speed, slow dial<br/>slow stop<br/>Turntable height 82mm Film frame rate<br/>3m/min<br/>20kg adjustable pressure pressure top<br/>Working pressure 0.4-0.7Mpa<br/>Cylinder stroke 800mm<br/>Control system PLC control<br/>Work auto / manual interchangeable<br/>Power / Power 1PH220VAC,<br/>50/60Hz,20A,1.35kw<br/>Dimensions 2565 * 1500 * 2535MM<br/>Weight 730kg</p>  | <p>Wood case</p> |
| <p>N-2000RY</p>                               |  | <p>Wrapping Specification (500-1200)<br/>× (500-1200) mm<br/>Turntable size φ1500/φ1650/φ<br/>1800mm/φ2000mm (optional)<br/>Turntable height 85mm height from the<br/>ground<br/>Package Height 1800mm<br/>(2000mm/2200mm/2400mm optional)<br/>Top pressure stroke<br/>800mm/1000mm/1200mm (optional)<br/>Packaging efficiency 20-40 Torr /hour<br/>Turntable speed 0-12rpm speed<br/>frequency adjustable turntable slowstart<br/>/ slow stop<br/>Turntable bearing (max) 2000kg<br/>Film pre-stretch film carriage rack<br/>system, the proportion of pre-stretch<br/>up to 250%, automatic film feeding<br/>DC drive system</p> | <p>Wood case</p> |

|  |   |  |                  |
|--|---|--|------------------|
| <p>G-AUTO- 02<br/>Automatic<br/>stretch<br/>wrapping<br/>machine</p> |    | <p>Wheel diameter:1650mm or 1800mm<br/>The effective packing height<br/>2100mm, orl 2400mm, 2600mm<br/>Turntable bearing 2000kg<br/>The packing efficiency Torr / h 20-30<br/>Rotary speed 0-15rpm, ariable<br/>frequency adjustable speed, rotary<br/>corrosion corrosion stop<br/>Table height 136mm<br/>Working pressure 0.4-0.7Mpa<br/>The top film mechanism of lifting speed<br/>3m/min<br/>The top film drawing mechanism of film<br/>speed 12m/min<br/>The top film size width 1700mm, length<br/>adjustable<br/>The film frame lifting speed 3m/min<br/>The control system of PLC control<br/>Remote control work Power<br/>/power3PH380VAC, 50/60Hz, 20A, 3kw<br/>Dimensions of 2960* 2625* 3100MM</p>                                 | <p>Wood case</p> |
| <p>N-2000RM<br/>wrapping<br/>machine<br/>machine</p>                 |  | <p>Wrapping Size L (500-1200) mm ×<br/>W (500-1200) mm<br/>Turntable size φ1650<br/>Turntable height 95mm height from the<br/>ground<br/>Package Height 1800mm<br/>Packaging efficiency 20-40 Torr /hour<br/>Turntable speed 0-12rpm speed<br/>frequency adjustable turntable slow<br/>start / slow stop<br/>Turntable bearing (max) 900kg or less<br/>Film pre-stretch film carriage rack<br/>system, the proportion of pre-stretch up<br/>to 250%, automatic film feeding DC<br/>drive system<br/>Lifting column double chain structure,<br/>vertical speed adjustable frequency<br/>Control system PLC control, number of<br/>layers, the number of adjustable height<br/>and turntable auto-sensing automatic<br/>reset<br/>Weight 750kg</p> | <p>Wood case</p> |

|  |   |   |                  |
|--|---|---|------------------|
| <p>N-600F stretch wrapping machine</p>             |    | <p>1 Dimension: 1350 * 600 * 1940mm (at actual size based)<br/>                 2 Wrapping size: L600 * W600 * H350-400mm<br/>                 3 Packaging efficiency :20-40 / hour<br/>                 4 wheel height :550-600mm<br/>                 5 turntable bearing: 100kg<br/>                 6 top pressure device: mechanical pressure arm, safe and stable<br/>                 7 Total power: 0.55kw<br/>                 8 Power supply voltage: 220V (single phase)<br/>                 9 Turntable speed: 0 to 12 rev / min<br/>                 10 Weight: 260kg</p>   | <p>Wood case</p> |
| <p>N-2000R pallet Pre-LAC stretch wrapper</p>      |  | <p>Wrapping Specification (500-1200)mm × (500-1200) mm<br/>                 Turntable size φ1500<br/>                 Turntable height 85mm height from the ground<br/>                 Package Height 1800mm<br/>                 Packaging efficiency 20-40 Torr /hour<br/>                 Turntable speed 0-12rpm speed frequency adjustable turntable slow start / slow stop<br/>                 Turntable bearing (max) 2000kg<br/>                 Film pre-stretch film carriage racksystem, the proportion of pre-stretch up to 250%, automatic film feeding DC drive system<br/>                 Lifting column double chain structure, vertical speed adjustable frequency;<br/>                 Control system PLC control, number of layers, the number of adjustable height and turntable auto-sensing automatic reset<br/>                 Weight 750kg</p> | <p>Wood case</p> |
| <p><b>Cigarette case film wrapping machine</b></p> |   |   |                  |

|  |   |  |                  |
|--|---|--|------------------|
| <p>SX-200 film wrapping machine for cigarette box and Cosmetic box</p>           |    | <p>Model: SX-200<br/>         Packaging materials: BOPP cigarette film (with optional gold wire)<br/>         Packing speed: 15 to 30 bags / min<br/>         Max packing size: L (40-200) × W(30-100) × H (10-80) mm<br/>         Weight: 180kg<br/>         Power supply: 220V<br/>         Using gas source: 5KG<br/>         Machine size: L1200 * W700 *900mm</p> | <p>Wood case</p> |
| <p>SX-300 film wrapping machine for cigarette box and Cosmetic box</p>           |    | <p>Model: SX-300<br/>         Packaging materials: BOPP cigarette film (with optional gold wire)<br/>         Packing speed: 15 to 30 bags / min<br/>         Max packing size L (80-300) × W(50-200)× H (20-100) mm<br/>         Weight: 230kg<br/>         Power supply: 220V<br/>         Using gas source: 5KG<br/>         Machine size: L1400 * W900 *1000mm</p> | <p>Wood case</p> |
| <p>S-300A full-auto film wrapping machine for cigarette box and Cosmetic box</p> |  | <p>Model: S-300A<br/>         Packaging materials: BOPP cigarette film (with optional gold wire)<br/>         Packing speed :40 to 80 packs / min<br/>         Max packing size :L 240 × W120 × H 60mm<br/>         Power and total power: 220V 50Hz5kw<br/>         Machine weight :500kg<br/>         Machine dimensions :L 2000 ×W700× H1400mm</p>                  | <p>Wood case</p> |
| <p><b>Shrink packing machine series</b></p>                                      |   |  |                  |
| <p>GNS-4525L Shrinking machine</p>   |  | <p>Power Supply:220/380V 50/60Hz 3P<br/>         Heater power:13kw<br/>         Heater power:10Kg<br/>         Working speed:0-12M/min<br/>         Tunnel size:L1200×W450×H250mm<br/>         Machine size:L1600×W715×H1520mm<br/>         Machine Weight:200kg</p>   | <p>Wood case</p> |

|  |   |   |                  |
|--|---|---|------------------|
| <p>GNL-5545T<br/>Manual L-sealing machine</p>    |    | <p>Model GNL-5545T<br/>Power supply 110/220V 1.2kw 50/60Hz<br/>Packing size L450×W400×H250mm<br/>Current size L550×W450mm<br/>Packing speed 800-1000pcs/h<br/>Machine dimension L1600×W775×H1000mm<br/>Machine weight 130kg<br/>High temperature and sticky free L bar sealing knife, sealing action without smoke and burn<br/>The seal is tidy and clean.<br/>Telfon covered on the sealing knife.<br/>Sealing time is accurately controlled by time delay</p>  | <p>Wood case</p> |
| <p>GNS-5030<br/>Automatic shrinking tunnel</p>   |  | <p>Max. packing size L700*W400*H200 (customizable for case size out of range)<br/>Stainless steel version Table height adjustable<br/>Interchangeable direction of machine per product feeding<br/>Machine body color is optional<br/>Bespoke plug apply to different area<br/>In-feed and out-feed conveyor is available Power: 110VAC, 380VAC, single phase, 3 phase<br/>Guiding pole device on conveyor is available Movable independent electric box<br/>control system Pressure device for flat and light product like book<br/>Teflon conveyor or stainless steel conveyor<br/>Combined with side sealing machine GNL-5545C</p> | <p>Wood case</p> |
| <p>GNS-5030LW<br/>Automatic Shrinking Tunnel</p> |  | <p>Model GNS-5030LW<br/>Power supply 380V、3<math>\phi</math>、50-60Hz<br/>Power 16kw<br/>Packing speed L1200×W450×H250mm<br/>highest temperature 250°C<br/>Turnl size L1500×W500×H300mm<br/>Machine dimension L2000×W1100×H1250mm<br/>Machine weight 650kg</p>   | <p>Wood case</p> |

|   |   |  |                  |
|---|---|--|------------------|
| <p>GNL-5545C L-bar sealing machine</p>                  |    | <p>Power 3 &amp; 380V 50/60Hz ≤ 3kw<br/>         Good size L infinitely<br/>         wide 300mm high 150mm<br/>         Many punch punch to the contraction of the air bag can be quickly discharged<br/>         Body parts material carbon steel, the key parts made of stainless steel and aluminum production, ensuring solid structure<br/>         Mechine Dimensions 1650 * 900 * 1550mm<br/>         Packing speed ranges depending on the package size (0-30 pcs / min)<br/>         Pressure 5.5KG/cm2</p> | <p>Wood case</p> |
| <p>GNL-4535 L-bar sealing machine</p>                   |   | <p>Power supply 220V、1 φ、50-60Hz<br/>         Packing size L+H≤500mm/ (H≤100mm)<br/>         Product W+H /tunnel size L550×W450mm<br/>         Packing speed 1-25pcs/min<br/>         Air compressing 5.5kg/cm³<br/>         Max current 10A<br/>         Net weight 250kg<br/>         Machine dimension L1830×W850×H1550mm</p>   | <p>Wood case</p> |
| <p>GNS-4525 Shrinking machine</p>                       |  | <p>Power Supply:220/380V 50/60Hz 3P<br/>         Heater power:10kw<br/>         Heater power:10Kg<br/>         Working speed:0-12M/min<br/>         Tunnel size:L1000×W450×H250mm<br/>         Machine size:L1300×W715×H1455mm<br/>         Machine Weight:185kg</p>   | <p>Wood case</p> |
| <p><b>Flap carton sealer series (hot melt glue)</b></p> |   |  |                  |

|   |   |   |                  |
|---|---|---|------------------|
| <p>GN-F02 Two Flap carton sealer (hot melt glue)</p>                    |    | <p>Type:GN-F02<br/>Capacity:57 boxes / min<br/>Total Power:0.37kw+1.6kw<br/>Electrical:AC220V 50HZ<br/>Net Weight:250kg Eternal<br/>Dimension:2100*910*1300mm<br/>APPLICable size:L100-320*W40-250*H25-100mm<br/>Materials: Hot melt adhesive</p>   | <p>Wood case</p> |
| <p>GN-F01 Semi-automaiton Single Flap carton sealer (hot melt glue)</p> |    | <p>Sealing speed 10 boxes /min<br/>Power supply 220v<br/>The size range for paper<br/>L80-300 × W44-200 × H25-80mm</p>  | <p>Wood case</p> |
| <p>GN-F03 Automation Two Flap carton sealer (hot melt glue)</p>         |  | <p>Sealing speed: 47 boxes / min<br/>Power supply: AC220 50HZ<br/>Total power: 1.97KW<br/>Vertebral sub-interval: 380mm<br/>Applicable carton size range:<br/>length:100-210mm Width :40-250<br/>high:25-80mm<br/>Dimensions: L1200 * W910 *H1000mm<br/>Custom designed for the amount of small business, the machine can work 24 hours, the failure rate is very low, all 304 stainless steel will never rust;</p> | <p>Wood case</p> |